

Behavioral Health Bed



FABRICATION & MATERIAL

Our headboards, footboards, and side rails are made out of 100% solid lumber. The posts are 1¾" thick x 3¼" wide. The joints are doweled and screwed to prevent any joints from opening up. The deck is ¾" plywood and is finished on both sides. The seam around the deck's perimeter is caulked to prevent liquids from seeping through. The side rails and deck supports are assembled together with cleats and this entire assembly is bolted to the headboard and footboard with 8 bolts per end. The levelers are ¾" diameter threads that will hold up to the weight of the bed and occupant with a static load rating of 800 lbs. TAA and Berry compliant with complete manufacturing in the U.S.A.

COLORS & FINISH

Home-like appearance (non-institutional) with the following standard finishes available: Oak, Cherry, or Walnut Customer may request other finishes to match existing beds and case goods. Sam Tucker does not guarantee the color and finish will match existing furniture.

PERFORMANCE TEST STANDARDS

Product tested to 800 lb static load.

ASSEMBLY

The bed is shipped fully assembled.

INSTALLATION

No installation is required for fully assembled units. Optional casters and bolt down method will include a complete set of instructions.

MAINTENANCE

Routine maintenance recommends Spic & Span Disinfecting All-Purpose Spray and Glass Cleaner by Procter and Gamble(FH/H/2005/JWJA-6JNPT2) and Virex II 256 (US) by Johnson Diversey (4329).

